

L-100

100 Watt Rad-Hard LED Luminaire

*Radiation certified
CB, CE, FCC certified*

Product flyer, Version 2.0, November 2021

Nuclear grade High-Bay LED Luminaire.

L-100 latest generation of high radiation and high temperature resistant series of LED products, proudly created and made by DITO Lighting, Slovenia, EU.

L-100 is a nuclear grade High-Bay LED Luminaire, designed to be used in moderate to high radiation, high temperature areas.

The Luminaire is simplified, yet more affordable, cost effective version of his older brother, the **H-100**. They are sharing the same mechanical, photometric and electrical properties.

The housing is made of anodized aluminium. The Luminaire is very light, easy to handle and is preferred choice for less demanding nuclear applications.

Typical applications are Hot-Cell lighting, spent fuel storage and processing facilities, industrial nuclear facilities.

L-100 is tested for TID of **50 kGy** gamma, combined with **5×10^{13} neutron/cm² 1MeV (Si)** equivalent neutron fluence.

L-100 is fully potted, without trapped air inside, therefore insensitive to sudden ambient pressure changes.



Soft mounting of the electronics means high seismic capacity, no sensitivity to vibrations and excellent protection against water, hot steam and other chemicals.

Complete electronics (driver) is located inside the Luminaire. The unit is connected directly to the mains, without any external boxes mounted elsewhere outside radiation area. The Luminaire is designed for simple upgrading of existing mature lighting technologies on one-to-one basis. In most cases no rewiring is needed.

For latest, up to date information please visit:

www.dito-lighting.com
info@dito-lighting.com

L-100

100 Watt Rad-Hard LED Luminaire



Specifications:

Rated power:	100 W
Rated voltages:	100-277 V AC or DC
Power factor:	> 0.9
Luminous flux:	> 16.000 lm
CCT:	5000 K
CRI:	> 80
Luminaire efficacy:	> 160 lm/W
Electronics location:	internal
Housing material:	Aluminium
Optics protection:	Silicone
Ingress protection:	IP 65
Impact protection:	IK 07
Ambient temperature:	-20 °C to +80 °C
Weight:	2.4 kg
Dimensions:	dia 320 × 208 mm

Warranty: 5 years

In compliance with (partial list):

MIL-STD-883, Method 1017 neutrons
MIL-STD-883, Method 1019 gamma
ESA ESCC No. 22900 gamma
IEEE 344 -2013
IEC 60980
2014/30/EU (EMC)
2014/35/EU (LVD)

Radiation tolerance:

Gamma:	5×10^4 Gy
Neutrons 1MeV (Si):	5×10^{13} n/cm ²

Reliability (environment: GB @ 50 °C):

Calculation method:	MIL-217F N2
MTBF:	3.758.857 h
Predicted lifetime:	> 22 years
Confidence level:	95 %

Notes:

Irradiation tests performed inside the core of the TRIGA MkII research reactor with the representative NPP spectrum.

The product is available with different input voltages ranging from 100 to 277 VAC or VDC, 50 or 60 Hz.

Custom cable length and custom Luminaire holder are available on request.