

# H-50 Gen IV

## 50 Watt Rad-Hard LED Luminaire



Product flyer, Version 1.1, April 2019

## Generation IV Rad-Hard LED Luminaire.

**H-50** is a member of extremely high radiation, extremely high temperature resistant series of LED products, proudly created and made by DITO Lighting, Slovenia, EU.

**H-50** is a nuclear, military, medical and space grade low-bay LED Luminaire, designed to be used in high radiation, high temperature areas. The Luminaire is available in Stainless Steel housing. The product is compatible with typical DBA and LOCA scenario. Main application for the **H-50** is lighting inside the RB of the NPP.

**H-50** is tested for TID of **500 kGy** gamma, combined with  **$5 \times 10^{14}$  n/cm<sup>2</sup> 1MeV (Si)** equivalent neutron fluence.

**Generation IV** can operate at high ambient temperatures:

- 60 °C - normal operation
- 80 °C - operational for 350 hours
- 170 °C - non operational for 24 hours

**H-50** is small, light, extremely efficient 50 W LED Luminaire, designed for simple one-to-one replacement of the existing tungsten or fluorescent based fixtures. LEDs are protected with soft, high temperature, 100 % shatter proof, browning proof, silicone optics.



Proprietary electronics is based on full discrete design without integrated circuits, electrolytic capacitors and optocouplers. Predicted lifetime is more than 20 years. Mission profile 24/7 at 50 °C ambient temperature.

The product is fully potted, without any trapped air inside, therefore insensitive to external pressure changes.

Internal electronics is soft mounted, protected against seismic shocks, vibrations, water, hot steam and most chemicals.

For latest, up to date information please visit:

[www.dito-lighting.com](http://www.dito-lighting.com)  
[info@dito-lighting.com](mailto:info@dito-lighting.com)



Published by DITO Lighting.  
DITO reserves the right to make changes without prior notice.

DITO Lighting logo is registered trademark.  
**H-100** and **H-50** are registered models.  
Copyright © DITO Lighting 2019. All rights reserved.

# H-50 Gen IV

## 50 Watt Rad-Hard LED Luminaire



### Specifications:

Nominal power:	50 W
Nominal voltage:	230 V AC or DC
Power factor:	> 0.95
Luminous flux:	> 8500 lm
CCT:	5000 K
CRI:	> 80
Overall Luminaire efficacy:	> 170 lm/W
Electronics efficiency:	> 90.0 %
Housing:	Stainless Steel
Optics protection:	Silicone
Ingress protection:	IP 68, 69K
Impact protection:	IK 08
Ambient temperature:	-20 °C to +60 °C
Weight:	3.3 kg
Dimensions:	dia 240 × 125 mm
Warranty:	5 years

### In compliance with (partial list):

MIL-STD-883, Method 1017 neutrons  
MIL-STD-883, Method 1019 gamma  
ESA ESCC No. 22900 gamma  
IEEE 344 -2013  
IEC 60980  
2014/30/EU (LVD)  
2014/35/EU (EMC)

### Radiation tolerance:

Gamma:	$5 \times 10^5$ Gy
Neutrons 1MeV (Si):	$5 \times 10^{14}$ n/cm <sup>2</sup>

### LOCA compatibility:

Ambient operational:	80 °C / 350 h
Ambient non operational:	170 °C / 24 h

### Seismic capacity:

Frequency range:	1 to 35 Hz, random
Base excitation:	> 10 g @ any axis

### Reliability (environment: GB @ 50 °C):

Calculation method:	MIL-217F N2
MTBF:	3.758.857 h
Predicted lifetime:	> 22 years
Confidence level:	95 %

### Notes:

Irradiation tests performed inside the core of the TRIGA MkII nuclear research reactor with the representative NPP spectrum.

The product is also available with other input voltages.