

# Industrial-100HBS Gen III®

100 Watt High Bay LED Luminaire

*Extremely Reliable  
Extremely Heavy Duty  
Extremely Efficient*

Product flyer, Version 2.0, Rev A, November 2018

## Generation III Heavy Duty Industrial LED Luminaire.

**Industrial-100HBS Gen III®** is third generation of high performance, heavy duty and high temperature resistant series of LED products, proudly created and made by DITO Lighting, Slovenia, EU.

**Industrial-100HBS Gen III®** is industrial grade LED Luminaire, designed to be used in harshest industrial, high temperature environment. The Luminaire is simplified, yet more affordable version of his older brother, world's best nuclear grade Luminaire, the **H-100HBS Gen III®**. The mechanical, photometric and electrical properties of both are the same. Industrial version has no nuclear qualification. Nevertheless the Luminaire can still survive gamma doses of up to 500 Gy.

The housing is made out of aluminium. Overall weight is 1.5 kg, without any sharp edges, therefore very easy to handle. Customized holders are available on request.

Overall system efficacy is more than 160 lm/W.

Available with two types of silicone optics - medium and wide. Different types of optics enable simple one-to-one replacement of mature lighting technologies in almost any lighting scenario.

Silicone optics is flexible, has operational temperature range of over 200 °C, is 100 % shatter



proof and chemically stable.

**Generation III** has fully vented housing. Therefore insensitive to sudden ambient pressure changes. Soft mounting of the electronics means high seismic capacity, no sensitivity to vibrations and excellent protection against water, hot steam and other chemicals.

Proprietary electronics is based on full discrete design without integrated circuits, electrolytic capacitors and opto couplers. Predicted lifetime is more than 20 years. Mission profile 24/7 at 50 °C ambient temperature.

For latest, up to date information please visit:

[www.dito-lighting.com](http://www.dito-lighting.com)  
[info@dito-lighting.com](mailto:info@dito-lighting.com)



Published by DITO Lighting.  
DITO reserves the right to make changes without prior notice.

DITO Lighting logo is registered trademark.  
**H-100HBS®** and **H-50LBS®** are a registered model.  
Copyright © DITO Lighting 2018. All rights reserved.

# Industrial-100HBS Gen III<sup>®</sup>

100 Watt High Bay LED Luminaire



## Specifications:

Nominal power:	100 W
Nominal voltage:	230 V AC or DC
Power factor:	> 0.95
Luminous flux:	> 16.000 lm
CCT:	5000 K
CRI:	> 80
Overall Luminaire efficacy:	> 160 lm/W
Electronics efficiency:	> 90.0 %
Housing:	Aluminium
Optics protection:	Silicone
Ingress protection:	IP 65
Impact protection:	IK 08
Ambient temperature:	-20 °C to +80 °C
Weight:	1.5 kg
Dimensions:	dia 330 × 124 mm

Warranty: 5 years

## In compliance with (partial list):

MIL-STD-883, Method 1017 neutrons  
MIL-STD-883, Method 1019 gamma  
ESA ESCC No. 22900 gamma  
IEEE 344 -2013  
IEC 60980  
EN 55015, EN 61547  
IEC/EN 60598-1, IEC/EN 60598-2-1  
IEC/EN 61347-1, IEC/EN 61347-2-13

## Radiation tolerance:

Gamma:	$5 \times 10^2$ Gy
Neutrons 1MeV (Si):	$5 \times 10^{10}$ n/cm <sup>2</sup>

## Seismic capacity:

Frequency range:	1 to 35 Hz, random
Base excitation:	> 10 g @ any axis

## Reliability (environment: GB @ 50 °C):

Calculation method:	MIL-217F N2
MTBF:	3.758.857 h
Predicted lifetime:	> 22 years
Confidence level:	95 %

## Notes:

Irradiation tests performed inside the core of the TRIGA MkII research reactor with the representative NPP spectrum.

The product is also available with US input voltage 120 V AC 60 Hz or 120 V DC.